

TECHNICAL SPECIFICATION

ELECTRICAL SUPPLY:

Cleaning controller - 24V DC/110/230V 1ph 50hz (by client)
Solenoid Valve - 24V DC

CONSTRUCTION:

- Mild steel
- BS.2660/7/078 Ral7032, light grey

COMPRESSED AIR:

Cleaning Pressure - 6 bar max.
Consumption - 5.1 m³/hr
(Based on 15 sec interval & 100msec. pulse)

FILTER MEDIA

Various media systems available to suit dust characteristics. (See quotation).

OPTIONS:

- ATEX certified
- Differential Pressure Monitor
- Filter Regulator
- Stainless Steel
- Special Paint Finish
- Alternative electrical supplies

DSR (dirty side removal) - Filter removal from below

Model	Total Filter Area m ²	Duty @ 1.5m/min	Duty @ 2.0m/min	'A' Dim
SFJ2-0.5-03	1	90	120	850
SFJ2-1-06	2	180	240	850
SFJ2-1.6-10	3.2	288	384	1250

VENTMATIC 120 SERIES



SFJ2 VENTING FILTER FAN ASSISTED (DSR)

Drawn: R.G.	Date: 1/11/08	Drawing No: D188	Rev: D
-------------	---------------	------------------	--------



**DUST COLLECTORS
DUST CONTROL SYSTEMS
CARTRIDGE FILTER ELEMENTS
MAINTENANCE & COSHH SURVEYS**

Web : www.dustcheck.co.uk
Email : sales@dustcheck.co.uk
Phone : 01782 599454



This drawing is private and confidential and is the property of Dustcheck LTD. It must not be copied or loaded or used for manufacturing or tendering purposes without the written consent of Dustcheck LTD.

Certificate No: 4064/03
026