

UNIT	MEDIA AREA m <sup>2</sup>
SFJC6-3.5-10VU	21
SFJC7-3.5-10VU	24.5

**TECHNICAL SPECIFICATION**

**ELECTRICAL SUPPLY:**

Cleaning controller - 24v DC / 110/230v 1ph 50hz (by client)  
Solenoid Valve - 24v DC

**CONSTRUCTION:**

- Mild Steel.
- Hot Dipped Galvanised (Filter Body).
- RAL 7032 Weatherproof Paint (Clean Section, Filter Plate & Jet Tubes).
- See Quotation.

Pressure Rating : 2 Barg Pressure Shock Resistant

**COMPRESSED AIR:**

- Pressure - 6 bar max.
- Consumption - 11.7 m<sup>3</sup>/hr (Based on 15 sec interval & 100msec. pulse)

**FILTER MEDIA**

Various Media Systems Available To Suit Dust Characteristics. (See Quotation).



**OPTIONS:**

- ATEX Certified
- Differential Pressure Monitor
- Filter Regulator
- Stainless Steel
- Special Paint Finish
- Alternative Electrical Supplies
- Mounting Spigot/Flange



**DUST COLLECTORS**  
**DUST CONTROL SYSTEMS**  
**CARTRIDGE FILTER ELEMENTS**  
**MAINTENANCE - COSHH - LEV SURVEYS**

Web : [www.dustcheck.com](http://www.dustcheck.com)  
Email : [sales@dustcheck.com](mailto:sales@dustcheck.com)  
Phone : 01782 599454



This drawing is private and confidential and is the property of Dustcheck LTD. It must not be copied or loaded or used for manufacturing or tendering purposes without the written consent of Dustcheck LTD.

Title:			
<b>SFJC VU CSR VENTING UNIT (2 BARG PRESSURE SHOCK RESISTANT)</b>			
Drawn:	Date:	Drawing No:	Rev:
R.G.	8/4/15	D209	A